



TIANGXI
COMPONENTS

田溪電子元器件

制 品 規 格 SPECIFICATION					
顧客 CUSTOMER				口径 SIZE	36 MM
型 号 MODEL NO.	顧客型号 CUSTOMER'S NO.				
	本公司型号 MAKER' NO.		A365K816BDKR	样品编号 NO.	24498
编号 NO.	项目 ETEM	规格 SPEC		测定条件 TEST COND	
1	音圈阻抗 VOICCOH.IMP	8 Ω ±15%		At 1.0v 800Hz	
2	动作 OPERATION	MUST BE NORMAL		AT.PROGRAM.SOURCE 1 W	
3	异常音 SWEEP TEST	MUST BE NORMAL		SIN WAVE 2.0 V	
4	最低共振频率 RESONANT FREQ(FO)	500 Hz ±20%		WITHOUT BAFFLE	
5	出力音压 OUTPUTS..P.L.	MEANVALUEAT90 ±3dB		AT/1W ON ZXISCALCULATED FROM/1M MEASUREMENT	
6	实效频率范围 FREQ RESPONSE	Fo 7 kHz -10dB		ATO 0.8 1.0 1.2 1.5kHz	
7	额定频率范围 RATED FREQRANG	Fo 7 kHz		MAX DEVIATION dB	
8	额定输入功率 RATED POWER INPUT	1 W			
9	最大功率 MAX POWER INPUT	1.5 W			
10	失真率 DISTORTION	5%MAX		RATED POWER INPUT 1000Hz	
11	连续试验 LOAD TEST	AFTER TEST MEET ITEM M2&3		NOISE 1 W 24 HOURS	
12	耐热试验 HEAT TEST	AFTER TEST MEET ITEM M2&3		50 ±2℃ 20/25%R. H. 5HOURS	
13	耐湿试验 HUMIDITY TEST	AFTER TEST MEET ITEM M2&3		40 ±2℃ 90/95%R. H. 5HOURS	
14	耐寒试验 COLD TEST	温度 -25℃		16 小时放置 1 小时后	
15	磁束密度 FLUX DENSITY	GAUSS			
16	磁铁 MAGNET	主磁 Φ12.5 X Φ X1.3mm 负磁		OZ OZ	
17	重量 WEIGHT	g			
承 认 APPROVED BY		制 作 DESIGNED BY		核 对 CHECKED BY	

型号: A365K816BDKR



型号: A365K816BDKR

